Listing and Amendments to the Claims

This listing of claims will replace the claims that were published in the PCT Application:

- 1. (currently amended) Outdoor unit of a reception terminal including a return channel, eharacterized in that wherein the return channel (BUC) comprises:
- a local oscillator (10)-providing a signal with a frequency that can be selected from at least two frequencies,
- a transposition means (X2) that transposes a signal to be transmitted using the signal provided by the local oscillator,
- a wideband filtering means (11)—that allows through signals whose frequency corresponds to the transposed signal independently from the frequency of the local oscillator, and
- a waveguide element (12, 30, 40)-having a cover (31, 32, 43, 45)-that depends on the frequency selected for the local oscillator.
- 2. (currently amended) Outdoor unit according to claim 1, characterized in that wherein the waveguide cover transforms the waveguide (30, 40) into a band rejector filter that rejects a bandwidth corresponding to a leak of the transposition frequency in the wideband.
- 3. (currently amended) Outdoor unit according to one of claims 1 or 2, characterized in that claim 1, wherein the cover is either a flat cover (31), or a cover (34) including slot-coupled resonant cavities.
- 4. (currently amended) Outdoor unit according to one of claims 1 or 2, characterized in that claim 1, wherein the waveguide comprises resonant cavities (42) coupled by slots (41), and in that the cover (43, 45) is either a flat cover (45), or a cover (43) comprising elements that electrically plug the slots.
- 5. (currently amended) Outdoor unit according to one of claims 1 to 4, characterized in that claim 1, wherein the local oscillator comprises means for selecting the oscillation frequency.

EXPRESS MAIL LABEL NO. EL 962134863 US Customer No. 24498

PF030146

6. (currently amended) Outdoor unit according to claim 5, characterized in that wherein the means for selecting the oscillation frequency is either a manual switch or a command from an indoor unit or terminal.